

Digital Printing Portfolio

EFI™ UV Inkjet

Fasson® product constructions shown have been evaluated by Avery Dennison and EFI and are recommended based upon the existing printer ink system utilized at the time of testing. Additional product constructions are available.

These products are available through our EXACT™ and Ready Width™ service programs. The one-slit roll minimum and next-day shipment are a great complement to the short run/quick turn capabilities of digital presses. Please contact your Avery Dennison sales representative for assistance.

Spec#	Facestock	Adhesive	Liner	EFI Jetrion® 4900	EFI Jetrion® 4950LX
Prime Paper					
53664	55# Semi-Gloss UV Inkjet FSC®	AT20	40#SCK	●	●
B4973	55# Semi-Gloss UV Inkjet FSC®	C4510	40#	●	●
54387	Bright Gold Foil	C4500	40#SCK	●	TBD
54385	Bright Silver Foil	C4500	40#SCK	●	TBD
53459	Dull Silver Foil	AT20	1.2 Mil PET	●	TBD
54386	Dull Silver Foil	C4500	40#SCK	●	TBD
02391	FasPrism™ Iridescent	S246	40#SCK	●	TBD
54384	Matte Litho FSC®	C4500	40#	●	●
18444	Matte Litho FSC®	R5195	40#SCK	●	●
03558	Matte Litho FSC®	S246	40#CK	●	●
53352	MaxFlex™ Bright Silver	AT20	40#SCK	●	●
53356	MaxFlex™ Bright Silver	C2075	40#SCK	●	●
54394	MaxFlex™ Bright Silver	C4500	40#	●	●
12906	Trans-Therm® 1C	S2501	40#CK	●	TBD
Prime Film					
B7350	2 Mil Clear BOPP TC	S7000ER	1.2 M PET	●	●
B7348	2 Mil Clear BOPP TC	S7000ER	40# BG	●	●
B7764	2 Mil Metallized BOPP TC	S7000ER	1.2 M PET	●	●
B7740	2 Mil White BOPP TC	S7000ER	1.2 M PET	●	●
B7741	2 Mil White BOPP TC	S7000ER	.92M PET	●	●
B7655	2.4 Mil White BOPP TC	S7000ER	1.2M PET	●	●
B7729	2.4 Mil White BOPP TC	S7000ER	40# BG	●	●
B8019	High Performance FasClear TC	S7000ER	1.2M PET	●	●
B7735	High Performance PRIMAX TC	S7000ER	1.2M PET	●	●
B7763	2 Mil Metallized BOPP TC	S692N-ER	1.2M PET	●	●
B7761	2.3 Mil White BOPP TC	S692N-ER	1.2M PET	●	●
B7760	2.3 Mil White BOPP TC	S692N-ER	40# BG	●	●
B7816	2.6 Mil White BOPP TC	S692N-ER	40# BG	●	●
B7693	2.6 Mil White BOPP TC	S692N-ER	1.2M PET	●	●
B7796	Global Co-Ex Clear TC	S692N-ER	PET 30	●	●
B8022	Global Co-Ex White TC	S692N-ER	PET 30	●	●

Spec#	Facestock	Adhesive	Liner	EFI Jetrion®		EFI Jetrion® UL® 969 w/ Inks	
				4000	4950LX	4000	4950LX
Durables							
77923	2 Mil Bright Chrome Polyester TC	S8025	50# SCK	TBD	TBD	I/O	I/O
77921	2 Mil Clear Polyester TC	S8025	50# SCK	TBD	TBD	I/O	I/O
78387	2 Mil Matte Chrome Polyester TC	S8001	50# SCK	TBD	●	I/O	I/O
77922	2 Mil Matte Chrome Polyester TC	S8025	50# SCK	TBD	●	I/O	I/O
79534	2 Mil Matte Chrome Polyester TC	S8049	50# SCK	TBD	●	I/O	I/O
72828	2 Mil White Printable PET	S333	50# SCK	●	●	-	-
78385	2 Mil White Polyester TC	S8001	50# SCK	TBD	●	I/O w/OL	I/O w/OL
77920	2 Mil White Polyester TC	S8025	50# SCK	TBD	●	I/O w/OL	I/O w/OL
79453	2 Mil White Polyester TC	S8049	50# SCK	TBD	●	I/O w/OL	I/O w/OL
78981	2 Mil White Polyester TCD	S8025	50# SCK	TBD	TBD	I/O w/OL	I/O w/OL
C0733	2.3 Mil White BOPP TC	S8001	50# SCK	●	●	Indoors	Indoors
78401	3 Mil Synthetic Paper	S8001	50# SCK	●	●	Indoors	Indoors
79648	4 Mil White Vinyl TCD	S8025	50# SCK	TBD	●	I/O w/OL	I/O

Spec#	Facestock	Adhesive	Liner	EFI Jetrion®		EFI Jetrion® BS 5609 Sec. 3	
				4000	4950LX	4000	4950LX
Drum Label							
79480	2.6 Mil Synthetic Paper	S8020	50#SCK	TBD	TBD	Passed	TBD
79572	3.7 Mil Smudgeproof Kimdura®	S4600	50#SCK	●	TBD	Passed	Passed
72197	4 Mil TransCode®	S475	50#SCK	TBD	TBD	Passed	Passed

- Recommended: Substrate meets Avery Dennison proprietary print testing standards. To earn our recommendation, a specification must demonstrate good print quality, readability and durability. In addition, Durables specs must pass a modified version of cross hatch test ASTM D3359.
- Application Specific: May require further customer-specific testing in order to confirm appropriateness for an application.
- Not Recommended: Indicates one or more of the characteristics failed the graded characteristics within the Avery Dennison test standards.

UL® 969 w/Inks: UL recognized with EFI 4000 and 4950LX inks. UL recognition with inks allows label adoption into an existing UL file. Refer to Avery Dennison UL-Recognized Components Guide for specific details regarding conditions of acceptability. The guide can be found at www.label.averydennison.com/durablegoods.

I/O w/ OL: Indoors/Outdoors with addition of overlaminate.
Spec# 77844: 1 Mil Clear Print Treated PET/S8020/40#BG.

NOTE: As label graphics and performance requirements vary, we encourage end application testing of all materials prior to use. This statement does not constitute a warranty.

Testing recommended for wine papers.



label.averydennison.com

ADV# 493 07/2025

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison products are sold subject to Avery Dennison's general terms and conditions of sale found at label.averydennison.com/en/home/terms-and-conditions.html.

