

## Fasson® Vellum Elite/S2492/CCK80Wh

Spec# / **AW0326**

Last Modified: 16-Aug-2010

### Facestock

A white, machine finished, woodfree-printing paper.

Basis Weight 60 g/m<sup>2</sup> TAPPI T410  
Caliper 75 µm TAPPI T411

### Adhesive

S2492 is a general-purpose permanent, emulsion acrylic adhesive featuring high cohesive strength, which is necessary for LCJ applications.

### Typical Performance Data

Initial Tack	12.5 or tear N/25mm	FTM 9 glass
Peel Adhes. 90°	9.0 or tear N/25mm	FTM 2 st.st.
Min. appl. temp.	5°C	
Service temp.	-20°C to 80°C subject to facestock limitations	

### Food Industry Labels

The adhesive complies with FDA regulations (section 175.105) for indirect food contact.

### Liner

CCK80 is a white one side clay-coated kraft paper, featuring uniform thickness, toughness and tear resistance as well as good layflat.

Basis Weight 80 g/m<sup>2</sup> ISO 536  
Caliper 80 µm ISO 534

### Laminate

Total Caliper 165 µm +/- 10%

### Applications and Uses

The product is designed for the manufacture of continuous forms products for use in high speed impact printers. The construction has excellent fanfolding and refolding properties, even in high speed wide web EDP printers.

Specially formulated release coating provide high release force required for preventing the converted labels from pre-dispensing, especially small size ones.

The facestock's surface structure provides excellent print resolution. The product is ideal for label applications requiring variable information such as address, instruction and inventory labels, labels for office use and many other applications.

S2492 adhesive has been designed to give good adhesion to plastic and paper substrates on which the mailing address label is applied.

### Printing / Converting

The facestock provides excellent print quality by all the usual printing techniques.

CCK80 liner exhibits very good layflat property and uniform caliper which is required for good die cutting in rotary and flat-bed.

### Shelf Life

One year when stored at 22°C and 50% R.H.

### Statement of Practical Use

As with all pressure sensitive materials, this product should be tested thoroughly under end-use conditions to ensure it meets the requirements of the specific application.



Avery Dennison (Thailand) Ltd.  
Avery Dennison Singapore Pte. Ltd.  
P.T. Avery Dennison Indonesia  
Avery Dennison Materials Sdn. Bhd.  
ADC Philippines Inc.  
Avery Dennison (Vietnam) Limited

Tel: +66 2 750 2070 Fax: +66 2 750 2071  
Tel: +65 6349 0333 Fax: +65 6278 2455  
Tel: +62 21 893 6033 Fax: +62 21 893 6031  
Tel: +60 3 8925 0901 Fax: +60 3 8925 0903  
Tel: +63 2 916 6816 Fax: +63 2 682 8243  
Tel: +84 8 3816 4639 Fax: +84 8 3816 4638

### Warranty

Information concerning Products are based upon tests believed to be reliable but do not represent a guarantee or warranty. Products are provided on the basis that any Purchaser has independently determined the suitability of the Products and Purchaser's purposes. The Company warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year of delivery (but not afterwards), upon notification thereof within seven (7) days of such appearance and substantiation that the Products have been stored and applied in accordance with the Company standards, the Company shall within a reasonable period correct such defects by providing a suitable replacement without charge at the Company's plant or at the location of the Products (at the Company's election) provided however, if the Company in its sole discretion determines that replacement is not commercially practical, the Company may issue a credit in favour of the Purchaser in an amount not to exceed the purchase price actually paid for the Products. Any implied warranty of merchantability fitness for particular purpose or other warranty of quality, whether express or implied by law, is hereby

excluded to the extent permitted by law. In no event shall the Company be liable for any incidental, indirect or consequential damages including, but not limited to, loss of profit, loss of use or loss of capital. The remedies of the Purchaser set forth herein are exclusive, and the total potential liability of the Company arising out of any contract of or from the manufacture, sale, delivery, resale, installation or use of any products shall not exceed the purchase price of the products upon which liability is based.