

Product Data Sheet FR Zig Zag TR / S2000 / BG40W

No Imprint / A12302-1000

Issue date: 1 March 2011

Facestock

A white machine finished and surface sized wood free printing paper.

Basis Weight 75/m² ISO 536 ISO 534 Caliper 0.080 mm

Adhesive

S2000 is a general purpose permanent acrylic emulsion adhesive.

Liner

BG40W is a special EDP glassine paper.

60 g/m² Basis Weight ISO 536 0.055 mm ISO 534 Caliper

Laminate

Total Caliper 0.155 mm +- 10%

PERFORMANCE DATA

Initial Tack >400 N/m FTM 9 glass >280 N/m Peel Adhesion 90° FTM 2 st.

Minimum application temp. +5°C

Service temp. -20°C to +80°C

N.B.: All data to be considered as typical values.

Adhesive performance

S2000 is a clear, permanent adhesive featuring excellent UV resistance and weatherability together with good adhesion performance even on apolar substrates.

Applications and use

Computer printable labels offering good dimensional stability and lay flatness as well as good interfolding characteristics. Designed specifically for use in continuous forms laser printers.

The above does not represent any guarantee or warranty and the Purchaser must independently determine the suitability of the products for the Purchaser's purposes.

Conversion / Printing

Good computer printablity where an absorbent surface allows fast drying of ribbon printed inks. Good laser printability. Excellent die cutting, sprocket punching, stripping and fan folding. Tight release from backing to prevent premature label dispensing during processing.

1 Year if stored at 22°C and 50 % relative humidity.

Statement of practical use

As with all pressure sensitive materials, this product should be tested thoroughly under end-use conditions to ensure it meets the requirements of the specific application.

Toll Free: 08000 AVERY

Johannesburg Tel: +27 11 249 5700 Fax: 0860 AVERY Fax: +27 11 472 2715

Durban

Cape Town

Tel: +27 31 792 6400 Tel: +27 21 534 0985 Fax: +27 21 534 0986 Fax: +27 31 792 6416 South Africa

Tel: +27 11 249 5700 Fax: +27 11 472 2770

South America Tel: +317 1 579 4100 Tel: +54 11 4014 2200 Fax: +54 11 4014 2225 Fax: +317 1 579 4180

Asia Pacific Tel: +852 2802 9618 Fax: +852 2588 1344

North America

Tel: +800 944 8511 (U.S. & Canada) Tel: +52 55 5565 0100 (Mexico)

Information concerning Products are based upon tests believed to be reliable but do not represent a guarantee or warranty. Products are provided on the basis that any Purchaser has independently determined the suitability of the Products and Purchaser's purposes. The Company warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year of delivery (but not afterwards), upon notification thereof within seven (7) days of such appearance and substantiation that the Products have been stored and applied in accordance with the Company standards, the Company shall within a reasonable period correct such defects by providing a suitable replacement without charge at the Company's plant or at the location of the Products (at the Company's election) provided however, if the Company in its sole discretion determines that replacement is not commercially practical, the Company may issue a credit in favour of the Purchaser in an amount not to exceed the purchase price actually paid for the Products. Any implied warranty of merchantability fitness for particular purpose or other warranty of quality, whether express or implied by law, is hereby excluded to the extend permitted by law. In no event shall the Company be liable for any incidental, indirect or consequential damages including, but not limited to, loss of profit, loss of use or loss of capital. The remedies of the Purchaser set forth herein are exclusive, and the total potential liability of the Company arising out of any contract of or from the manufacture, sale, delivery, resale, installation or use of any products shall not exceed the purchase price of the products upon which liability is based.

Europe