

Product Services Guide

South Africa
July 2025

Need more information?

Business Support Team

08000 AVERY (28379)

Mon to Thu 8.00am – 4.30pm

Fri 8.00am – 4.00pm

(excluding South African public holidays)

Avery Dennison Business Support Team is ready to answer your questions. Call us to discuss product availability, ordering process, or anything else you need.

Account Business Managers

Cape Town

Andrew Zwicky +27 82 908 5107

Johannesburg

Andrew Zwicky +27 82 908 5107

Durban

Kuben Naidoo +27 82 886 3533

Technical Support

South Africa

Scott Leatherbarrow +27 82 903 8776

Quality Department

South Africa

Thelma Ratshikhopha +27 82 883 6189

Account Enquiries

South Africa

Ferial Isaacs +27 11 249 5700

Contact us:

South Africa

Cnr. Winze Drive and Leader Avenue
Stormill Ext 4
Roodepoort
1709


Data & Specification Sheets

label.averydennison.com

Should you require more technical data for any of our products, you can download specification sheets from our website. If you cannot find the specification sheet you are after, please contact your Avery Dennison representative.

Introduction

Welcome to the July 2025 Product Services Guide. This Guide was created to provide you with a single document to inform you of the core product portfolios of Avery Dennison Label and Packaging Materials South Africa.

| Item | Facestock | Adhesive | Liner | Service Program / Width (mm) | MOQ (m ²) | Length (m) | Stocking Location | Sustainable ADvantage | Comments |
|---------------------|-------------------|------------|--------|------------------------------|-----------------------|------------|-------------------|--|---------------------|
| MACHINE COAT | | | | | | | | | |
| AL89350F | *SEMIGLOSS 80 FSC | S2045 (HM) | BG40WH | FULL DECKLE 1525mm | 1525 | 1000 | JHB |  Responsibly sourced. Renewable content (Adhesive Contains 30% Renewable Content) | 0°C Min. Appl. Temp |
| | | | | EXACT | 1000 | 1000/ 2000 | DBD CTD | | |

How to read the Product Services Guide

Item:
The item number identifies the product on your delivery documents and invoices.

Facestock:
Identifies the facestock used in the construction.

Adhesive:
Identifies the particular adhesive used in the construction.

Liner:
When liner codes end in the letter 'N' this signifies a nil imprint. PET liners never have a backprint.

FSC® certified facestock or liner
* Only the products identified as such count with Forest Stewardship Council® certification.



Service Program:
The service program details how the product is sold to the market.

- FULL DECKLE
Signifies the product is sold with the complete web width and the minimum length of 1000 metres.
- EXACT
Items are sold in any width with fixed lengths that vary for each program.
- Ready Width
Offers slit rolls in set widths and lengths.

MOQ (sqm):
All orders must meet Minimum Order Quantity. SQM is determined by multiplying width by length.


Length (LM):
Identifies the length in lineal meters, offered in a service program

Stocking Location:
Indicates which AD site the product is stocked in

Sustainable Advantage:
Why the product is part of the Sustainable Advantage portfolio.



Look for the marked
Sustainable ADvantage
products in this
Product Services Guide



Contains Recycled or Renewable Content

Give a second life to what has already been used.

Facestocks and liners that include post-industrial waste or post-consumer recycled content.


Renewable Content - The renewable sources can be used for facestocks, Adhesives and/or liners, and/or other coatings with at least 30% of the content of that specific component.



Reduction in the use of materials

Use only what is necessary.

Thinner facestock, adhesive, or liner that uses less raw materials to be manufactured



Enables Recycling, Reuse or Compostability

What we use can be used again.

Solutions that enhance recyclability and enable reuse and recycling of packaging as well as the recycling and composting of label waste





















Responsibly sourced

Products sourced from a supply chain that shows care for people and the environment.













Film made from renewable alternatives and paper certified by FSC® or other organizations



Prime Papers

| Item | Facestock | Adhesive | Liner | Service Program / Width (mm) | MOQ (m ²) | Length (m) | Stocking Location | Sustainable ADvantage | Comments | | |
|--------------|-----------------------|--|------------|------------------------------|-----------------------|------------|-------------------|---|---|--|---------------|
| MACHINE COAT | | | | | | | | | | | |
| AL89350F | * SEMIGLOSS 80 FSC | S2045 (HM) 0°C Min. Appl. Temp | BG40WH | FULL DECKLE 1525mm | 1525 | 1000 | JHB |   | Responsibly sourced, Renewable content (Adhesive Contains 30% Renewable Content) | | |
| | | | | EXACT | 1000 | 1000/ 2000 | DBD CTD | | | | |
| ALY89350F | * SEMIGLOSS 80 FSC | S2045 (HM) 0°C Min. Appl. Temp | BG40BR | EXACT | 1000 | 1000/ 2000 | JHB DBD CTD |   | Responsibly sourced, Renewable content (Adhesive Contains 30% Renewable Content) | | |
| AW04270F | * SEMIGLOSS 70 FSC | S2045 (HM) 0°C Min. Appl. Temp | BG33WH | FULL DECKLE 1525mm | 1525 | 1000 | JHB DBD |   | Responsibly sourced, Renewable content (Adhesive Contains 30% Renewable Content). Reduction in material use: | EasyCut adhesive | |
| PTF6845 | SEMIGLOSS 80 | S2045 (HM) 0°C Min. Appl. Temp | PET23 | FULL DECKLE 1000mm | 1000 | 1000 | JHB DBD |   | Renewable content (Adhesive Contains Renewable Content). Reduction in the use of materials (Liner) | | |
| AW2433F | * SEMIGLOSS 80 FSC | S2345 (HM) High tack 0°C Min. Appl. Temp | BG40BR | FULL DECKLE 1500mm | 1500 | 1000 | JHB DBD CTD |  | Responsibly sourced | High tack | |
| ALYF6849F | SEMIGLOSS 80 FSC | S445N(HM) Super tack | BG40BR | FULL DECKLE 1500mm | 1500 | 1000 | DBD CTD |   | Responsibly sourced, Renewable content (Adhesive Contains 30% of the Renewable Content) | Super tack | |
| AW0425F | * MC SEMIGLOSS GP FSC | S1002 (EM) | BG33WH | FULL DECKLE 1525mm | 1525 | 1000 | JHB | CTD |   | Responsibly sourced, Reduction in the use of materials (Liner) | |
| | | | | EXACT | 1000 | 1000/2000 | DBD | | | | |
| ALE8845 | FASLITHO | S2045 (HM) 0°C Min. Appl. Temp | BG40WH | FULL DECKLE 1500mm | 1500 | 1000 | DBD |  | Renewable content (Adhesive Contains 30% Renewable Content) | | |
| ALE8879 | FASLITHO | S2345 (HM) High tack | BG40WH | FULL DECKLE 1000mm | 1000 | 1000 | DBD | | | High tack | |
| AN589ZAF | * SEMIGLOSS 80 FSC | C2075 (HM) Freezer grade | BG40BR | FULL DECKLE 1000mm | 500 | 500 | JHB | CTD |   | Responsibly sourced, Renewable content (Adhesive Contains 30% Renewable Content) | Freezer grade |
| CO111 | * rMC FSC | R5000 (EM) Removable | BG40BR FSC | FULL DECKLE 1000mm | 500 | 500 | JHB DBD CTD |   | Renewable content (Facestock contains 30% recycled components from industrial materials). Responsibly sourced | Removable | |

Prime Papers

| Item | Facestock | Adhesive | Liner | Service Program / Width (mm) | MOQ (m ²) | Length (m) | Stocking Location | Sustainable ADvantage | Comments |
|-------------------|--------------------------|------------------------------------|---------------|------------------------------|-----------------------|------------|-------------------|--|-----------|
| LIGHT WEIGHT | | | | | | | | | |
| AM18451F | LW60 FSC | S2050 (HM) | BG40W IMP | FULL DECKLE 1000mm | 500 | 500 | JHB DBD CTD |   Reduction in material use(Facestock), Responsibly sourced | |
| VELLUM | | | | | | | | | |
| BC679 | * TRANSFER VELLUM FSC | S2000NG (EM) | BG40BR | FULL DECKLE 2000mm | 2000 | 1000 | DBD |  Responsibly sourced | |
| LLYF3831 | FASMATT VELLUM | S2045 (HM) 0°C Min. Appl. Temp | CK40 | FULL DECKLE 1500mm | 1500 | 1000 | JHB DBD CTD |  Renewable content (Adhesive Contains 30% Renewable Content) | |
| ALB4690 | TRANSFER VELLUM | S2345 (HM) High tack | BG40WH | FULL DECKLE 1000mm | 1000 | 1000 | JHB DBD |  Reduction in material use(Facestock) | High tack |
| CK618 | TRANSFER VELLUM FSC | R5000 (EM) Removable | BG40BR | FULL DECKLE 1000mm | 500 | 500 | JHB DBD |  Responsibly sourced | Removable |
| METALISED PAPER | | | | | | | | | |
| AL326 | * MP PLUS SILVER FSC | S2045N (HM) 0°C Min. Appl. Temp | BG40BR | FULL DECKLE 1000mm | 500 | 500 | DBD CTD |   Responsibly sourced, Renewable content (Adhesive Contains 30% Renewable Content) | |
| SPECIALITY PAPERS | | | | | | | | | |
| AA875F | * FASTYRE PLUS FSC | TS79 (HM) | * BG40W IMP | FULL DECKLE 1000mm | 500 | 500 | JHB DBD CTD |   Responsibly sourced, Renewable content (Adhesive Contains 30% Renewable Content) | |
| SW4106 | MC SEMIGLOSS PB | 2 x S2090 (HM) | 2 x BG40W IMP | FULL DECKLE 1500mm | 750 | 500 | JHB DBD CTD | | |
| AMA1450F | * SEMIGLOSS FSC COVERALL | S2050 (HM) | BG40WH IMP | FULL DECKLE 1500mm | 750 | 500 | DBD CTD |  Responsibly sourced, | |
| AM89400ZA | DUKUZA BOARD 160G | S2050 (HM) | BG40 | FULL DECKLE 1000mm | 500 | 500 | CTD |  Reduction in material use (Facestock) | |






Prime Films

| Item | Facestock | Adhesive | Liner | Service Program / Width (mm) | MOQ (m ²) | Length (m) | Stocking Location | | Sustainable ADvantage | Comments |
|-------------------|--------------------------|-----------------------------------|----------|------------------------------|-----------------------|------------|-------------------|--|---|------------|
| CONFORMABLE FILMS | | | | | | | | | | |
| AF186 | PE85 TOP WH | S692N (EM) | * BG40WH | FULL DECKLE 2000mm | 2000 | 1000 | DBD | | Reduction in material use, Enables Recycling, Reuse or Compostability (Monomaterial for labelled HDPE containers) | |
| AF187 | PE85 TOP CL | S692N (EM) | * BG40WH | FULL DECKLE 2000mm | 2000 | 1000 | DBD | | Reduction in material use, Enables Recycling, Reuse or Compostability (Monomaterial for labelled HDPE containers) | |
| AF172 | PE100 TOP WH | S277 (EM) | BG40WH | FULL DECKLE 2000mm | 2000 | 1000 | DBD | | | |
| RIGID WHITE FILMS | | | | | | | | | | |
| AL09033 | PP60 TOP WHITE CAVITATED | S2045 (HM) 0°C Min. Appl. Temp | BG33WH | EXACT | 1000 | 1000/2000 | JHB DBD CTD | | Responsible sourced, Renewable content (Adhesive Contains 30% Renewable Content) | |
| BW8018 | PP60 TC WHITE | SR3013 (EM) | BG33WH | FULL DECKLE 1530mm | 1530 | 1000 | JHB DBD CTD | | CleanFlake™ Enables Recycling, Reuse or Compostability, Reduction in material use (Liner) | |
| ALYF1843 | PP60 TOP WHITE CAVITATED | S2045 (HM) 0°C Min. Appl. Temp | BG40BR | FULL DECKLE 1530mm | 1530 | 1000 | JHB DBD | | Renewable content (Adhesive Contains 30% Renewable Content) | |
| BW8333 | PP60 TOP WHITE CAVITATED | S692N (EM) | BG33WH | FULL DECKLE 1530mm | 1530 | 1000 | JHB DBD CTD | | Enables Recycling, Reuse or Compostability (Monomaterial for labelled HDPE containers) | |
| BW8012 | PP50 TOP WHITE CAVITATED | S692N (EM) | BG33WH | FULL DECKLE 1500mm | 1500 | 1000 | CTD | | Enables Recycling, (Monomaterial for labelled HDPE containers), Reduction in material use | |
| AB074 | PP60 TOP WHITE | S692N (EM) | * BG50WH | FULL DECKLE 2000mm | 2000 | 1000 | DBD | | Enables Recycling, Reuse or Compostability (Monomaterial for labelled HDPE containers) | |
| ALYF1839 | PP60 TOP WHITE CAVITATED | S2345 (HM) High tack | BG40BR | FULL DECKLE 1530mm | 1530 | 1000 | JHB DBD CTD | | Responsible sourced, Renewable content (Adhesive Contains 30% Renewable Content) | High tack |
| AB303 | PP60 TOP WHITE CAVITATED | S445N (HM) Super tack | BG45WH | FULL DECKLE 1000mm | 500 | 500 | JHB DBD | | Responsible sourced, Renewable content (Adhesive Contains 30% Renewable Content) | Super tack |

Prime Films

| Item | Facestock | Adhesive | Liner | Service Program / Width (mm) | MOQ (m ²) | Length (m) | Stocking Location | | Sustainable ADvantage | Comments |
|-------------------------------|--------------------------|-----------------------------------|-----------|------------------------------|-----------------------|------------|-------------------|--|--|---------------|
| RIGID WHITE FILMS (continued) | | | | | | | | | | |
| AF733ZA | PP60 TOP WHITE CAVITATED | C2075 (HM) Freezer grade | BG40BR | FULL DECKLE 1000mm | 500 | 500 | JHB DBD CTD | | Renewable content (Adhesive Contains 30% Renewable Content) | Freezer grade |
| RIGID CLEAR FILMS | | | | | | | | | | |
| BW8019 | PP50 TC CLEAR | SR3013 (EM) | BG40Y | FULL DECKLE 1530mm | 1530 | 1000 | JHB DBD CTD | | CleanFlake™ Enables Recycling, Reuse or Compostability, Reduction in material use (Liner) | |
| CH878 | PP50 TOP CLEAR | S7000ER (EM) | rPET23 | FULL DECKLE 1980mm | 1980 | 1000 | DBD | | CleanFlake™ Enables Recycling, Reuse or Compostability, Reduction in material use (Facestock), Contains Recycled (Liner contains up to 30% recycled PCR) | |
| AX150R | PP60 TOP CLEAR | S4000N (EM) | rPET30 | FULL DECKLE 1000mm | 1000 | 1000 | DBD CTD | | Contains Recycled (Liner contains up to 30% recycled PCR) | |
| ALYF0601 | PP50 TOP CLEAR | S2045 (EM) 0°C Min. Appl. Temp | BG40BR | FULL DECKLE 1000mm | 1000 | 1000 | JHB DBD CTD | | Reduction in material use, Renewable content (Adhesive Contains 30% Renewable Content) | |
| AM11070ZA | PP50 TOP CLEAR | S2345 (HM) High tack | BG40W IMP | FULL DECKLE 1000mm | 1000 | 1000 | DBD CTD | | Reduction in material use (Facestock) | High tack |
| BW8300 | PP50 TOP CLEAR | S692N (EM) | BG33BR | FULL DECKLE 1500mm | 1500 | 1000 | JHB DBD CTD | | Enables Recycling, Reuse or Compostability (Monomaterial for labelled HDPE containers), Reduction in material use (Facestock) | |


Prime Films

| Item | Facestock | Adhesive | Liner | Service Program / Width (mm) | MOQ (m ²) | Length (m) | Stocking Location | | | Sustainable ADvantage | Comments | |
|------------------|-----------------------|------------|--------------|------------------------------|-----------------------|------------|-------------------|-----|-----|---|---|------------------------------|
| METALLISED BOPP | | | | | | | | | | | | |
| AMF9601 | PP50 METALISED SILVER | S2060 (HM) | BG40WH IMP | FULL DECKLE 1000mm | 1000 | 1000 | JHB | DBD | CTD |   | Reduction in material use (Facestock). Renewable content (Adhesive Contains 30% Renewable Content) | |
| SW8507F | PP50 GLOSS SILVER TC | S692N (EM) | * BG40WH IMP | FULL DECKLE 1500mm | 1500 | 1000 | JHB | DBD | CTD |  | Reduction in material use (Facestock) | |
| CJ406 | PP50 TOP SILVER | S7400 (EM) | rPET23 | FULL DECKLE 1980mm | 1980 | 1000 | | DBD | |   | Reduction in material use (Facestock). Contains Recycled (Liner contains up to 30% recycled PCR). Reduction in the use of materials (Liner) | Transitioning to CK130 in Q3 |
| SPECIALITY FILMS | | | | | | | | | | | | |
| AM65241ZA | FOAMTAC | S2050 (HM) | BG40W | FULL DECKLE 1000mm | 500 | 500 | JHB | DBD | CTD | | | |




Variable Information Papers

| Item | Facestock | Adhesive | Liner | Service Program / Width (mm) | MOQ (m ²) | Length (m) | Stocking Location | | | Sustainable ADvantage | | Comments |
|------------------------|-----------------------------------|------------------------------------|-----------|------------------------------|-----------------------|------------|-------------------|---------|---|---|-----------------------------------|-----------|
| DIRECT THERMAL PAPER | | | | | | | | | | | | |
| ALYG6833F | ✱ DIRECT THERMAL TC FSC | S2045N (HM) 0°C Min. Appl. Temp | BG33BR | EXACT | 1000 | 1000/2000 | JHB | CTD |   | Responsibly sourced, Renewable content (Adhesive Contains 30% Renewable Content) | | |
| | | | | FULL DECKLE 1500mm | 1500 | 1000 | DBD | | | | | |
| NWP5900_58x65 | THERMAL TC25 LINERLESS - DRY EDGE | HP103 (HM) | LINERLESS | 24 ROLLS PER BOX | 20 BOXES | 58mmX65m | CTD | JHB | DBD |  | Reduction in material use (Liner) | |
| ALY55833R | ✱ rDT ECONOMY THERMAL 70 FSC | S2045N (HM) 0°C Min. Appl. Temp | BG33BR | FULL DECKLE 1500mm | 1500 | 1000 | JHB | DBD |   | Renewable content (Facestock contains 15% recycled components from industrial materials). Responsibly sourced, Renewable content (Adhesive Contains 30% of the Renewable Content) | | |
| ALY55845R | ✱ rDT ECONOMY THERMAL 70 FSC | S2045N (HM) 0°C Min. Appl. Temp | BG40BR | FULL DECKLE 1000mm | 1000 | 1000 | CTD | |   | Renewable content (Facestock contains 15% recycled components from industrial materials). Responsibly sourced, Renewable content (Adhesive Contains 30% of the Renewable Content) | | |
| AG177 | ✱ DIRECT THERMAL TC S8 FSC | S445N (HM) Super tack | BG40BR | FULL DECKLE 1000mm | 1000 | 1000 | JHB | DBD |  | Responsibly sourced | Super tack | |
| BU294ZAF | ✱ DT200HD PLUS TC FSC | C2075N (HM) Freezer grade | BG40BR | FULL DECKL 1525mm | 762 | 500 | JHB | CTD |   | Responsibly sourced, Renewable content (Adhesive Contains 30% Renewable Content) | Freezer grade. | |
| BU296 | ✱ THERM 200HD PLUS NP FSC | R5000N (EM) Removable | BG40BR | FULL DECKL 1000mm | 500 | 500 | JHB | DBD CTD |  | Responsibly sourced | | |
| THERMAL TRANSFER PAPER | | | | | | | | | | | | |
| ALYA8845 | FASTRANSFER ULTRA | S2045 (HM) 0°C Min. Appl. Temp | BG40BR | FULL DECKLE 1000mm | 1000 | 1000 | JHB | DBD CTD |  | Renewable content (Adhesive Contains 30% Renewable Content) | | |
| ALYB4845 | FASTRANSFER STANDARD | S2045N (HM) 0°C Min. Appl. Temp | BG40BR | FULL DECKLE 1000mm | 1000 | 1000 | DBD CTD | |  | Renewable content (Adhesive Contains 30% Renewable Content) | | |
| ALA8858 | FASTRANSFER ULTRA | S2345 (HM) High tack | BG40BR | FULL DECKLE 1000mm | 1500 | 1000 | JHB | DBD | | | | High tack |















Variable Information Papers

| Item | Facestock | Adhesive | Liner | Service Program / Width (mm) | MOQ (m ²) | Length (m) | Stocking Location | Sustainable ADvantage | Comments |
|--------------|-------------------|------------|------------|------------------------------|-----------------------|------------|-------------------|---|----------|
| INKJET PAPER | | | | | | | | | |
| OW2350 | GLOSS IJ PAPER | AP103 (EM) | BG40WH IMP | FULL DECKLE 1070mm | 268 | 250 | JHB CTD | | |
| LASER PAPER | | | | | | | | | |
| OW0053G | ✱ LASERPRO 70 FSC | S692N(EM) | CK55W | FULL DECKLE 210mm | 315 | 1500/3000 | JHB DBD CTD |  Responsibly sourced | |

Variable Information Films

| Item | Facestock | Adhesive | Liner | Service Program / Width (mm) | MOQ (m ²) | Length (m) | Stocking Location | Sustainable ADvantage | Comments |
|-----------------------|------------------------------|----------------------------------|------------|------------------------------|-----------------------|------------|-------------------|--|-----------|
| THERMAL TRANSFER FILM | | | | | | | | | |
| BW0053 | TTP MATT WHITE | S692N (EM) | BG40WH | FULL DECKLE 1000mm | 1000 | 1000 | JHB DBD |  Enables Recycling, Reuse or Compostability (Monomaterial for labelled HDPE containers) | |
| AL74680 | TTP MATT WHITE | S2345 (HM) High tack | BG40WH IMP | FULL DECKLE 1000mm | 1000 | 1000 | JHB DBD | | High tack |
| AF592 | PET50 WHITE | S695(EM) | BG45W | FULL DECKLE 1000mm | 500 | 500 | JHB |  Reduction in material use (Facestock) | |
| DIRECT THERMAL FILM | | | | | | | | | |
| NWS5203 | DIRECT THERMAL PP75 WHITE TC | HP103(HM) 0°C Min. Appl. Temp | BG40WH IMP | FULL DECKLE 1530mm | 1530 | 1000 | CTD |  Renewable content (Adhesive Contains 30% Renewable Content) | |
| INKJET FILM | | | | | | | | | |
| OZ2120 | 100um IJ SYN PAPER | AF101 | BG40WH IMP | FULL DECKLE 1530mm | 382 | 250 | JHB DBD CTD | | |

Wine Portfolio

| Item | Facestock | Adhesive | Liner | Service Program / Width (mm) | MOQ (m ²) | Length (m) | Stocking Location | Sustainable ADvantage | Comments |
|------------------|-------------------------------|-------------|-----------------|------------------------------|-----------------------|------------|-------------------|--|----------|
| GLOSS PAPER | | | | | | | | | |
| AW2141F | * CAST GLOSS PREMIUM FSC | S2000W (EM) | BG40WH | FULL DECKLE 1525mm | 1525 | 1000 | JHB CTD |  Responsibly sourced | |
| SW7060 | * Cast Gloss Elite FSC | S2030 (EM) | BG40 WH | FULL DECKLE 1525mm | 1525 | 1000 | CTD |  Responsibly sourced | |
| SW7083F | * CAST GLOSS ELITE FSC | S2030 (EM) | rPET23 | FULL DECKLE 1525mm | 1525 | 1000 | CTD |   Responsibly sourced. Reduction in the use of materials (Liner) | |
| SPECIALITY PAPER | | | | | | | | | |
| AU266 | WHITE COTTON | S2047N (HM) | * BG45WH | FULL DECKLE 1000mm | 500 | 500 | CTD |  Renewable content (Adhesive Contains 30% Renewable Content) | |
| AG600 | * LINEN FSC | S2047N (HM) | * BG45WH IMP | FULL DECKLE 1000mm | 500 | 500 | CTD |   Responsibly sourced, Renewable content (Adhesive Contains 30% Renewable Content) | |
| F29333 | * ARTISAN FSC | S2047 (HM) | BG40WH | FULL DECKLE 1525mm | 1525 | 1000 | CTD |   Responsibly sourced, Renewable content (Adhesive Contains 30% Renewable Content) | |
| CO385 | * NOBLE EXTRA WHITE rPLUS FSC | S2030 (EM) | * BG45WH HR FSC | FULL DECKLE 1000mm | 1000 | 1000 | CTD |   Responsibly sourced | |
| LB357 | * VERGE BLANC FSC | S2030 (EM) | * BG45WH FSC | FULL DECKLE 1000mm | 1000 | 1000 | CTD |  Responsibly sourced | |
| F12783 | * VINTAGE FSC | S2047N (HM) | BG40WH | FULL DECKLE 1525mm | 1525 | 1000 | CTD |   Responsibly sourced, Renewable content (Adhesive Contains 30% Renewable Content) | |

Operational Terms & Conditions

Any exceptions to the standards are subject to an upcharge unless otherwise noted

Core Diameter

- 76mm
- Specialties on Request

Splice Standard

- Up to 1000m: 1 splice
- 1000 – 2000m: 2 splices
- More than 2000m: 3 splices

Minimum Distance Between Splices and to Start/End of a Roll

200 m

Splice Tape

PVC Red/Brown Tape

Splice Indication

Number of splices is indicated on the roll label and position of splice indicated by stamp on side of the roll

Offcut Disposition

Customer will be charged for full deckle unless sales order is requested on Fasson Exact™ program

Slit Width

- Minimum slit width is 90mm
- Maximum slit width is 1500mm
- Maximum width dependent on master roll width

Slit Roll Width Tolerances

Width tolerance is +/- 1mm

Roll Length

- Minimum Standard roll length is 1000m
- Specialties 500m

Roll Length Tolerance

Roll length tolerance of +/- 10%

Maximum Roll Length

Approximately 2000m – dependent on product

Total Order Quantity

Order supplied +/- 5%

Packaging Method

Rolls will be horizontally or vertically packed

Roll Tag Labels

Roll Labels on outside of roll and one in roll core

Palletized deliveries

- All deliveries as required are palletized
- These pallets remain the property of Avery Dennison and need to be returned.

Maximum Stack Heights

1m

Minimum Order Quantity

- Standard MOQ is 1000m of the full material width
- Fasson Exact program MOQ is 1000m². Certain Specialties may be 500m²

Material Quality Matters

- Material to remain at the customer's premises until final testing/evaluations have been done
- Complaints are attended to within the stipulated life of the product as per material data sheet
- Response to complaints within 2 working days
- Resolution within 21 working days – dependent on type of complaint

Technical Support

- Technical support and product training available for both converters and end users
- Training is offered at ADSA discretion

Cut-off Times For Orders

- All orders received at or before 10am will be delivered within 24 hours unless confirmed otherwise
- Unless communicated otherwise, Orders serviced from our 2m deckle in DBN DC will be delivered in 48 hours for JHB Customers and 72 hours for CTN customers.
- Fasson EXACT products lead time is 2 working days to dispatch EXCEPT when product ordered is not offered at the local DC in which case transportation lead time of additional 2 working days applies.
- Collections from 09:00am – 15:00pm, Monday – Friday
- Customer must make collection arrangements at least 3 hours prior to collection
- Direct indent orders have 8 – 12 weeks lead time depending on freight mode and source

National Freight Charge

- Applicable freight charges:
- As per agreed pro-forma terms & conditions for exports orders
- Should customer require stock faster than the standard channel

Operational Terms & Conditions (continued)

Order Cancellation

- Not permitted once slit
- Fasson Exact Program sales order cancellation not permitted once Order Acknowledgment has been issued

Width Substitution

As agreed upon by both parties

Product Substitution

- Substitution with the nearest alternate product allowed in the event of stock shortage and agreed by both parties

Changes on Service Programs

- Please note that the release of this Product Services Guide happens once in a quarter, therefore this release does not mean or suggest or be understood in any way to mean that the service programs listed in this document will remain the same throughout the quarter
- Lookout for communications from our Customer Services for any Service Program changes that may happen after this release
- We encourage the frequent use of the MyAD portal for Service Programs as it will always reference the most recent as per available inventory

Damaged Product on Delivery

- Customers to inspect all products on delivery.
- Any damages to be acknowledged at the time of delivery by being noted on the Delivery Docket
- Avery Dennison approval required before material is picked up
- Failure to acknowledge at the time of delivery will be deemed that the damage occurred at the customer's premises

Customer Purchase Order

- Email Purchase Order to Avery Dennison Order Centre email address: ordercentre@eu.averydennison.com
- Customer Purchase Order should include the following information:
 - Purchase Order number.
 - Company Name / Account number.
 - Delivery address, Required date.
 - Item required, Quantity required & Price.
 - Name & title and contact number for Buyer.
- Once purchase order has been processed by Avery Dennison; an order acknowledgment will be emailed to the customer
- Failure to clearly supply these details may result in delays

Proof Of Delivery

Material to be checked. Delivery Docket signed and returned to driver/courier

Price increase

- 30 days notice period
- Notice period may change subject to exceptional circumstances

Avery Dennison
Label and Packaging Materials

South Africa

Johannesburg

Cnr. Winze Drive & Leader Avenue
Stormill Ext 4, Roodepoort 1709, Gauteng, Africa

Durban

24 Westmead Road,
Westmead, Pinetown, KwaZulu Natal

Cape Town

11 Assegai Road, Parow Industria
Parow, 7493, Western Cape

Kenya

WH 10 - 11, Saku Business Park
Mombasa Highway, Nairobi

Learn more at label.averydennison.com



#MakingPossible

© 2025 Avery Dennison Corporation. All rights reserved. The "Making Possible" tagline, Avery Dennison and all other Avery Dennison brands, product names and codes are trademarks of Avery Dennison Corporation. All other brands or product names are trademarks of their respective owners. Fortune 500® is a trademark of Time, Inc. Branding and other information on any samples depicted are fictitious. Any resemblance to actual names is purely coincidental.