


Finishing, Packaging and Shipping Standards

Standards apply to ORDERED roll footage, not actual roll footage

| Requirement | Condition | Standard | Comments |
|------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Pattern Gum | PS | Customer specified pattern | |
| Core Diameter | Most pressure sensitive constructions | 3" | Heavy wall cores and 6" cores on slit rolls are exceptions and require an upcharge. 6" cores are available on unslit masters, with no upcharge. |
| | PS film/film and laser and PS with LF/MF liners | 6" | 3" available with an upcharge. |
| | Fasson® Rapid-Roll® | 3" | 6" is available upon request, no upcharge required. |
| Maximum Number of Splices: (Special splice standards apply to Tamperfas™, SCANback™ and other Film/Specialty constructions). | | | |
| Two-Ply paper/paper, paper/film, film/paper and film/film | </=5k | 1 splice | |
| | 5001-10k | 2 splices | |
| | >10k | 3 splices | |
| Pattern Gum/Multi-ply constructions | </=5k | 3 splices | |
| | 5001-10k | 4 splices | |
| | >10k | 5 splices | |
| Splice Tape | All | Red Central 600-1-1/2" wide/Clear Central 400-3/4" wide. | Upcharge applies for all other tapes and approval necessary. |
| Splice Configuration | All | 3-tape splice is standard; 4-tape splice is standard for piggyback constructions. | |
| Splice Indication | All | No Indicators. | Will mark with arrow stamp, one or both sides, upon request, no upcharge required. Does not apply to Fasson EXACT™ or Ready Width™. |
| Unwind Direction Indication | All | No indicators. | Will mark with arrow stamp on outside of roll upon request, no upcharge required. Does not apply to Fasson EXACT™ or Ready Width™. |
| Min. distance between splices and to start/end of a roll | All | 500 ft. | |
| Slit Roll Width Tolerance | All | +/- 1/32" for full gum orders. +/- 1/16" for pattern gum orders. | |
| Total MSI Tolerance | Custom finish, Fasson Exact™, Ready Width™ | +/- 10%. | |
| | Custom Coat | +/- 10% for single pass orders with standard raw materials. | |
| | | +/- 15% for two pass orders with standard raw materials. | |
| | | +/- 20% for orders with the purchase of non-standard raw materials. | |
| Roll Quantity Tolerance | Fasson EXACT™, Ready Width™ | All rolls ordered must ship, even if total order MSI is within tolerance. | |
| Roll Length Tolerance | Custom finish, Fasson Exact™, Ready Width™ | +/- 10% | |
| Face In/Out | Non-EXACT™, Fasson Ready Width™ | Face out. | Face in available upon request, no upcharge required. Face in not recommended for constructions with face stocks that are sensitive to scratching (clear/clear, foils). |
| | Fasson EXACT™, Ready Width™ | Face out. | Face in not offered. |
| Roll Tag Labels | Non-EXACT™ | Labels located on the outside of the roll, not on the seam, inside the stretch wrap. | Labels applied in core, customer specific labels and blank labels are exceptions and require approval and an upcharge. |
| | Fasson EXACT™, Ready Width™ | | Special labeling requirements require approval and upcharge. |
| Pallet Size | P1 - 30L x 30W | All sites standard. | All rolls must fit completely within the confines of the pallet with no overhang. Roll diameters must be less than the width of the pallet.  |
| | P2 - 30L x 45W | All sites standard. | |
| | P3 - 40L x 40W | All sites standard. | |
| | P4 - 48L x 45W, 4-way entry | All sites standard. | |
| | P5 - 54L x 29W, 4-way entry | All sites standard. | |
| | P6 - 61L x 30W | All sites standard. | |
| | P7 - 48L x 40W, 4-way entry | All sites standard. | |
| | P8 - 36L x 36W | All sites standard. | |
| | P9 - 48L x 30W | All sites standard. | |
| Roll Configuration | All | Pancake | Will cradle pack for roll length equal/greater than 5000 ft, upon request, no upcharge. Cradle packing below 5000 ft requires upcharge. Cradle packing unavailable below 20" combined width due to safety issues. |
| Roll Widths per Pallet | All | Mixed widths per pallet with one width per stack. If less than sufficient quantity of a width to complete a stack, then widest rolls on bottom, narrowest rolls on top. | 1. If one width per pallet when reasonable is REQUESTED, no upcharge is applied. 2. If one width per pallet is REQUIRED, upcharge is applied to multiple width orders. In both situations, best fitting pallet will be used if preferred pallet size can not secure load. |
| Maximum Stack Height (additional stack height limitations may be imposed to ensure stability of pallet) | PS<10K | Up to 45" (including pallet height). | |
| | PS>= 10K | Up to 48" (including pallet height). | |
| | Fasson® Rapid-Roll® | Up to 48" (including pallet height). | |
| Packaging Method | All | Stretch wrap pallets - all plants. | Banding is standard on cradle packed rolls 10K and longer. Will band all cradle packed rolls upon request, no upcharge required. Carton packing, level stacking, vapor barriers, oversized headers, and core plugs are exceptions and require an upcharge. |
| | | In addition, FTW and GFD cocoon wrap roll stacks. | |
| Export Packaging | All | Available for shipments marked for export. | |
| Carrier Preferences | All | Contract carriers. | Non-contract carrier shipments must be customer collect, no approval necessary. |
| Certification Letter | All | Delivered with shipment available upon request, no approval necessary. | Certificate data is also available on the website. |
| Delivery Appointment | All | Non-standard | Customers can request that carriers call before delivering. |
| Customer Delivery Hours (Receiving) | All | Between 7am to 3pm customer's local time. | Specific delivery times are exceptions and require approval. |
| Delivery Instructions | All | Truckload (TL) or Less than Truckload (LTL). | Expedite and air freight are exceptions and require approval. |

Any exceptions to the above standards are subject to an approval process unless otherwise indicated and may include an upcharge. No exceptions to the above standards are applicable to Fasson EXACT™ and Ready Width™ orders.