

Spec#	Facestock	Adhesive	Liner	Width/Length (In/Ft.)	UV68 Ink	UV90 Ink
<b>Rapid Roll</b>						
75723	1079 Tyvek	NA	NA	EXACT/10500 Stock 48/1668	●	●
75724	1085D Tyvek	NA	NA	EXACT/5000 Stock 48/1668	●	●
78939	6 Mil White Static Cling TC	NA	NA	Stock 54/1668	●	●
77038	7Mil Polyart	NA	60#KK	Stock 60/1668	●	●
16801	8 Mil C1S Smudgeproof Kimdura	NA	NA	Stock 52/1668	●	●
<b>Durables</b>						
77923	2 Mil Bright Chrome Polyester TC	S8025	50# SCK	EXACT™/5000	-	●
77921	2 Mil Clear PET TC	S8025	50# SCK	EXACT™/5000	●	●
78387	2 Mil Matte Chrome Polyester TC	S8001	50# SCK	EXACT™/5000	●	●
77922	2 Mil Matte Chrome Polyester TC	S8025	50# SCK	EXACT™/5000	●	●
79534	2 Mil Matte Chrome Polyester TC	S8049	50# SCK	Custom 54/1000	●	●
78385	2 Mil White Polyester TC	S8001	50# SCK	EXACT™/5000	●	●
77920	2 Mil White Polyester TC	S8025	50# SCK	EXACT™/5000	●	●
79453	2 Mil White Polyester TC	S8049	50# SCK	EXACT™/2500	●	●
78981	2 Mil White Polyester TCD	S8025	50# SCK	EXACT™/5000	●	●**
72828	2 Mil White PRT PET	S333	50# SCK	EXACT™/5000	●	●
78403	2.3 Mil White BOPP TC	S8001	50# SCK	EXACT™/5000	●	●
78401	3 Mil Synthetic Paper	S8001	50# SCK	EXACT™/5000, 10000	●	●
79648	4 Mil White Vinyl TCD	S8025	50# SCK	Stock 54/1668	●	●**

● Recommended: Substrate meets Avery Dennison proprietary print testing standards. To earn our recommendation, a specification must demonstrate good print quality, readability and durability. In addition, Durables specs must pass a modified version of cross hatch test ASTM D3359.

● Application Specific: May require further customer-specific testing in order to confirm appropriateness for an application.

● Not Recommended: Indicates one or more of the characteristics failed the graded characteristics within the Avery Dennison test standards.

NOTE: As label graphics and performance requirements vary, we encourage end application testing of all materials prior to use. This statement does not constitute a warranty.

See the EXACT Card for current EXACT and Ready Width service program.

UL 969 w/ UV90 Inks: UL recognized with Domino UV90 inks. UL recognition with an ink system allows label adoption into an existing UL file. Refer to the Avery Dennison UL-Recognized Components Guide for specific details regarding conditions of acceptability.

Key:

I/O: Passes "Indoors/Outdoors" without addition of overlaminate.

I/O w/ OL: Passes "Indoors/Outdoors" with addition of Avery Dennison overlaminate.

e.g. Spec# 77844: 1 Mil Clear Print Treated PET/S8020/40#BG.

Indoors: Only tested for Indoors. Passes "Indoors" without addition of overlaminate. Not recommended for "Outdoor" applications.