



# Digital Printing Portfolio

## Durst Tau 330 UV Inkjet

Fasson® product constructions shown have been evaluated by Avery Dennison and Durst and are recommended based upon the existing printer ink system utilized at the time of testing. Additional product constructions are available.

These products are available through our EXACT™ and Ready Width™ service programs. The one-slit roll minimum and next-day shipment are a great complement to the short run/quick turn capabilities of digital presses. Please contact your Avery Dennison sales representative for assistance.

Spec#	Facestock	Adhesive	Liner	Width/Length (In./Ft.)	Tau 330
<b>PRIME PAPER</b>					
53664	55# Semi-Gloss UV Inkjet	AT20	40#SCK	EXACT™/5000	●
14532	Matte Litho FSC®	C2500	40#CK	EXACT™/5000	●
18444	Matte Litho FSC®	R5195	40#SCK	EXACT™/2500	●
03558	Matte Litho FSC®	S246	40#CK	EXACT™/5000	●
53352	MaxFlex™ Bright Silver	AT20	40#SCK	EXACT™/5000	●
53356	MaxFlex™ Bright Silver	C2075	40#SCK	EXACT™/10000	●
53355	MaxFlex™ Bright Silver	C2500	40#SCK	EXACT™/5000	●
				EXACT™/10000	●
<b>PRIME FILM</b>					
79628	2 Mil Clear BOPP UV Inkjet	S7000	1.2 Mil PET	Stock 78/1668	●
79636	2 Mil Clear BOPP UV Inkjet	S7000	40#BG	Ready Width™ 13/5000	●
78889	2 Mil Metallized BOPP TC	S7000	1.2 Mil iPET	EXACT™/5000	●
				EXACT™/10000	●
79101	2 Mil Metallized BOPP TC	S7000	40#BG	EXACT™/10000	●
79746	2 Mil White BOPP UV Inkjet	S7000	40#BG	Stock 78/1668	●
79634	2.3 Mil White BOPP UV Inkjet	S7000	1.2 Mil PET	Ready Width™ 13/5000	●
79635	2.3 Mil White BOPP UV Inkjet	S7000	40#BG	Ready Width™ 13/5000	●
76912	2.6 Mil White BOPP	S692N	40#BG	EXACT™/5000	●
78098	3 Mil White MDO	S692N	40#BG	EXACT™/5000	●
				EXACT™/10000	●
<b>WINE PAPERS</b>					
53381	56# MaxFlex™ Bright Silver	AT20	1.2 Mil PET	EXACT™/10000	●
53351	56# MaxFlex™ Bright Silver	S100R	44#PK	Ready Width™ 10/5000	●
				Ready Width™ 12/5000	●
19648	60# Classic Crest Solar White WS	AT20	1.2 Mil PET	EXACT™/5000	●
				EXACT™/10000	●
19657	60# Classic Crest Solar White WS FSC	S100R	1.2 Mil PET	EXACT™/5000	●
12623	60# Classic Crest® Solar White WS FSC®	S100R	44#PK	EXACT™/5000	●

Spec#	Facestock	Adhesive	Liner	Width/Length (In./Ft.)	Tau 330	UL® 969	UL® 969 w/ Inks
<b>DURABLES</b>							
77923	2 Mil Bright Chrome PET TC	S8025	50#SCK	EXACT/5000	●	I/O	I/O
77921	2 Mil Clear PET TC	S8025	50#SCK	EXACT/5000	●	I/O	I/O
78387	2 Mil Matte Chrome PET TC	S8001	50#SCK	EXACT/5000	●	I/O	I/O
77922	2 Mil Matte Chrome PET TC	S8025	50#SCK	EXACT/5000	●	I/O	I/O
79534	2 Mil Matte Chrome PET TC	S8049	50#SCK	CC 54/1000	●	I/O	I/O
78385	2 Mil White PET TC	S8001	50#SCK	EXACT/5000	●	I/O	I/O w/ OL
77920	2 Mil White PET TC	S8025	50#SCK	EXACT/5000	●	I/O	I/O w/ OL
79453	2 Mil White PET TC	S8049	50#SCK	Single Roll*/2500 Stock 54/1668	●	I/O	I/O w/ OL
78981	2 Mil White PET TCD	S8025	50#SCK	EXACT/5000	●	I/O	I/O w/ OL
72828	2 Mil White Print Treated PET	S333	50#SCK	EXACT/5000	●	I/O	I/O
78403	2.3 Mil White BOPP TC	S8001	50#SCK	EXACT/5000	●	Indoors	Indoors
78401	3 Mil Synthetic Paper	S8001	50#SCK	EXACT/5000	●	Indoors	Indoors
73952	4 Mil White Vinyl TC	S4600	50#SCK	EXACT/3300	●	I/O	I/O
79648	4 Mil White Vinyl TCD	S8025	50#SCK	Stock 54/1668	●	I/O	I/O
Spec#	Facestock	Adhesive	Liner	Width/Length (In./Ft.)	Tau 330	UL® 969	BS 5609 w/ Inks
<b>DRUM LABEL</b>							
79572	3.7 Mil Smudgeproof Kimdura®	S4600	50#SCK	EXACT/5000	●	-	Passed
72197	4 Mil TransCode®	S475	50#SCK	EXACT/5000	TBD	Indoors	Passed

\*Single Slit Roll Service Program: Available in any width by 2500 ft.

UL® 969: UL recognized with thermal transfer ribbons. Refer to specification data sheet for specific conditions of acceptability and ribbons tested.

UL® 969 w/Inks: UL recognized with Durst Tau 330 inks. UL recognition with inks allows label adoption into an existing UL file. Refer to Avery Dennison UL-Recognized Components Guide for specific details regarding conditions of acceptability. The guide can be found at [www.label.averydennison.com/durablegoods](http://www.label.averydennison.com/durablegoods).

I/O: Indoors/Outdoors

I/O w/ OL: Indoors/Outdoors with addition of overlamine, Spec# 77844: 1 Mil Clear Print Treated PET/S8020/40#BG

- Recommended: Substrate meets Avery Dennison proprietary print testing standards. To earn our recommendation, a specification must demonstrate good print quality, readability and durability. In addition, durables specs must pass a modified version of cross hatch test ASTM D3359.
- Application Specific: May require further customer-specific testing in order to confirm appropriateness for an application.
- Not Recommended: Indicates one or more of the characteristics failed the graded characteristics within the Avery Dennison test standards.



See the EXACT Card for current EXACT and Ready Width service program.

NOTE: As label graphics and performance requirements vary, we encourage end application testing of all materials prior to use. This statement does not constitute a warranty.

ADV# 430/16121, 09/2018, PDF

©2018 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, product names and codes are trademarks of Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. Personal and company names and other information on samples depicted are fictitious. Any resemblance to actual names and addresses is purely coincidental.



Label and Packaging Materials

**North Asia**  
5th Floor, Hongye Park  
1801 Hongmei Road,  
Xuhui District 200233,  
Shanghai, China  
+86 21 33951888

**South Asia Pacific and Sub-Saharan Africa**  
460 Alexandra Road,  
PSA Building  
#28-02/03, Singapore 119963  
+65 6430 7000

**Europe**  
Willem Einthovenstraat 11  
2342 BH Oegstgeest  
The Netherlands  
+31 85 000 2000

**Latin America**  
Rodovia Vinhedo-  
Viracopos, KM 77  
CEP 13280-000  
Vinhedo - SP, Brazil  
+55 19 3876-7600

**North America**  
8080 Norton Pkwy  
Mentor, OH 44060  
800.944.8511