

| Spec#              | Facestock                              | Adhesive | Liner       | Width/Length<br>(In./Ft.) | EFI Jetrion®<br>4900 | EFI Jetrion®<br>4950LX |
|--------------------|----------------------------------------|----------|-------------|---------------------------|----------------------|------------------------|
| <b>WINE PAPERS</b> |                                        |          |             |                           |                      |                        |
| 12623              | 60# Classic Crest® Solar White WS FSC® | S100R    | 44#PK       | EXACT™/5000               | ●                    | ●                      |
| 01533              | 60# Estate Label® No. 4 WS FSC®        | S100R    | 44#PK       | Ready Width™ 6/5000       | ●                    | ●                      |
|                    |                                        |          |             | Ready Width™ 10/5000      |                      |                        |
|                    |                                        |          |             | Ready Width™ 12/5000      |                      |                        |
| 19298              | 60# Matte Litho WS                     | AT20     | 44#PK       | EXACT™/5000               | ●                    | ●                      |
| 53381              | MaxFlex™ Bright Silver                 | AT20     | 1.2 Mil PET | EXACT™/10000              | ●                    | ●                      |
| 53351              | MaxFlex™ Bright Silver                 | S100R    | 44#PK       | Ready Width™ 10/5000      | ●                    | ●                      |
|                    |                                        |          |             | Ready Width™ 12/5000      | ●                    | ●                      |

| Spec# | Facestock | Adhesive | Liner | Width/Length<br>(In./Ft.) | EFI Jetrion® |        | EFI Jetrion® UL® 969 w/Inks |        |
|-------|-----------|----------|-------|---------------------------|--------------|--------|-----------------------------|--------|
|       |           |          |       |                           | 4000         | 4950LX | 4000                        | 4950LX |

## DURABLES

|       |                                  |       |                                    |               |     |     |          |          |
|-------|----------------------------------|-------|------------------------------------|---------------|-----|-----|----------|----------|
| 77923 | 2 Mil Bright Chrome Polyester TC | S8025 | 50# SCK                            | EXACT™/5000   | TBD | TBD | I/O      | I/O      |
| 77921 | 2 Mil Clear Polyester TC         | S8025 | 50# SCK                            | EXACT™/5000   | TBD | TBD | I/O      | I/O      |
| 78387 | 2 Mil Matte Chrome Polyester TC  | S8001 | 50# SCK                            | EXACT™/5000   | TBD | ●   | I/O      | I/O      |
| 77922 | 2 Mil Matte Chrome Polyester TC  | S8025 | 50# SCK                            | EXACT™/5000   | TBD | ●   | I/O      | I/O      |
| 79534 | 2 Mil Matte Chrome Polyester TC  | S8049 | 50# SCK                            | EXACT™/5000   | TBD | ●   | I/O      | I/O      |
| 72828 | 2 Mil White Printable PET        | S333  | 50# SCK                            | EXACT™/5000   | ●   | ●   | —        | —        |
| 78385 | 2 Mil White Polyester TC         | S8001 | 50# SCK                            | EXACT™/5000   | TBD | ●   | I/O w/OL | I/O w/OL |
| 77920 | 2 Mil White Polyester TC         | S8025 | 50# SCK                            | EXACT™/5000   | TBD | ●   | I/O w/OL | I/O w/OL |
| 79453 | 2 Mil White Polyester TC         | S8049 | Single Roll*/2500<br>Stock 54/1668 | EXACT™/5000   | TBD | ●   | I/O w/OL | I/O w/OL |
| 78981 | 2 Mil White Polyester TCD        | S8025 | 50# SCK                            | EXACT™/5000   | TBD | TBD | I/O w/OL | I/O w/OL |
| 78403 | 2.3 Mil White BOPP TC            | S8001 | 50# SCK                            | EXACT™/5000   | ●   | ●   | Indoors  | Indoors  |
| 78401 | 3 Mil Synthetic Paper            | S8001 | 50# SCK                            | EXACT™/5000   | ●   | ●   | Indoors  | Indoors  |
| 79648 | 4 Mil White Vinyl TCD            | S8025 | 50# SCK                            | Stock 54/1668 | TBD | ●   | I/O w/OL | I/O      |

| Spec#      | Facestock                    | Adhesive | Liner  | Width/Length<br>(In./Ft.) | EFI Jetrion®                                                                        |        | EFI Jetrion® BS 5609 Sec. 3 |        |
|------------|------------------------------|----------|--------|---------------------------|-------------------------------------------------------------------------------------|--------|-----------------------------|--------|
|            |                              |          |        |                           | 4000                                                                                | 4950Lx | 4000                        | 4950Lx |
| DRUM LABEL |                              |          |        |                           |                                                                                     |        |                             |        |
| 79480      | 2.6 Mil Synthetic Paper      | S8020    | 50#SCK | Stock 60/1668             | TBD                                                                                 | TBD    | Passed                      | TBD    |
| 79572      | 3.7 Mil Smudgeproof Kimdura® | S4600    | 50#SCK | EXACT™/5000               |  | TBD    | Passed                      | Passed |
| 72197      | 4 Mil TransCode®             | S475     | 50#SCK | EXACT™/5000               | TBD                                                                                 | TBD    | Passed                      | Passed |

See the EXACT Card for current EXACT and Ready Width service program.

- Recommended: Substrate meets Avery Dennison proprietary print testing standards. To earn our recommendation, a specification must demonstrate good print quality, readability and durability.
- Application Specific: May require further customer-specific testing in order to confirm appropriateness for an application.
- Not Recommended: Indicates one or more of the characteristics failed the graded characteristics within the Avery Dennison test standards.



UL® 969 w/Inks: UL recognized with EFI 4000 and 4950LX inks. UL recognition with inks allows label adoption into an existing UL file. Refer to Avery Dennison UL-Recognized Components Guide for specific details regarding conditions of acceptability. The guide can be found at [www.label.averydennison.com/durablegoods](http://www.label.averydennison.com/durablegoods).

I/O w/ OL: Indoors/Outdoors with addition of overlaminate, Spec# 77844: 1 Mil Clear Print Treated PET/S8020/40#BG.

NOTE: As label graphics and performance requirements vary, we encourage end application testing of all materials prior to use. This statement does not constitute a warranty.

ADV# 432, 16120, 08/2017, PDF

©2017 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, product names and codes are trademarks of Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. Personal and company names and other information on samples depicted are fictitious. Any resemblance to actual names and addresses is purely coincidental.



Label and  
Packaging Materials

**North Asia**  
5th Floor, Hongye Park  
1801 Hongmei Road,  
Xuhui District 200233,  
Shanghai, China  
+86 21 33951888

**South Asia Pacific and  
Sub-Saharan Africa**  
460 Alexandra Road,  
PSA Building  
#28-02/03, Singapore 119963  
+65 6430 7000

**Europe**  
Willem Einthovenstraat 11  
2342 BH Oegstgeest  
The Netherlands  
+31 85 000 2000

**Latin America**  
Rodovia Vinhedo-  
Viracopos, KM 77  
CEP 13280-000  
Vinhedo - SP, Brazil  
+55 19 3876-7600

**North America**  
8080 Norton Pkwy  
Mentor, OH 44060  
800.944.8511