

Spec#	Facestock	Adhesive	Liner	Width/Length (In./Ft.)	LX600	LX910	LX2000
Durable Film							
79348*	5 Mil Matte White Drum Label	S4600	50#SCK	EXACT™/2500,5000	●	●	●
79404	3 Mil Matte White Synthetic	S8001	50#SCK	EXACT™/2500	●	●	●
79119	2 Mil White Inkjet PET	S8001	50#SCK	Stock 54/1668	●	●	●
79330	3.2 Mil White Inkjet Vinyl	S730	50#SCK	Custom 54/4630	●	●	●
79673	5 Mil Matte Inkjet	S8001	50#SCK	Custom 60/4167	●	●	●
79724	3.5 Mil Matte White Synthetic WBIJ	S4600	50#SCK	EXACT/10000	●	●	●
Rapid Roll							
79812	Rapid-Roll® 7.5 Mil Kimdura WBIJ			Stock 58.75/1668	●	●	●
79816	Rapid-Roll® 6Mil C2S Premium Matte WBIJ FSC®			Stock 52.25/1668	●	●	●
79817	Rapid-Roll® 10Mil C2S Glossy WBIJ FSC®			Stock 52.25/1668	●	●	●
79932	Rapid-Roll® 9.5 Mil Kimdura WBIJ			Custom Coat 54.75/11000	●	●	●

- Recommended: Indicates these substrates meet Avery Dennison proprietary print testing standards. To earn our recommendation, a specification must have average or better print quality, readability, image traits and durability.
- Indicates substrates meet Avery Dennison print testing standards but may require further customer-specific testing in order to confirm their appropriateness for an application.
- Not Recommended: Indicates one or more of the characteristics failed the graded characteristics within the Avery Dennison test standards.

NOTE: As label graphics and performance requirements vary, we encourage end use application testing of all materials prior to use.

*Approved for BS 5609 Section 3 when printed with Primera pigment inks.