



# Select Solutions™ Safety and Warning Labels Portfolio

Reliable solutions designed to perform on broad range of surfaces commonly subjected to climate or chemical exposure.

Used in appliance, lawn and garden, automotive, electronics and medical device applications, safety and warning labels are critical to communicating the proper use and handling of equipment. They are also vital to protecting your brand from risk of litigation due to accidents or death.

How big is the risk? It is significant. For instance, according to the U.S. Consumer Products Safety Commission, there were more than 900,000 power tool and workshop equipment accidents reported from 1997-2002, with approximately 400,000 emergency room treated injuries each year.

Our Select Solutions Portfolio of durable, high performance Safety and Warning label materials can help mitigate these risks and safeguard your brand.

## Application Versatility

Whether for bare, painted, powder coated metals, or molded polymer parts, our film facestocks and adhesive combinations have been chosen for their ability to withstand harsh environments and outdoor exposures. Heat, cold, rain, snow, oils or gasoline... our Safety and Warning label materials perform well, offering consistent legibility and readability over the life of the labeled items, no matter the climate or environmental conditions. In fact, the majority of our Safety and Warning products are UL® recognized for UL 969 and cUL C22.2 standards having passed the 750 hour weathering test, as well as exhibiting resistance to common agents testing using gasoline, lubricating oils and harsh chemicals.

Because these labels are used in such a diverse range of equipment applications in multiple end use conditions, the Select Solutions Safety and Warning Label portfolio offers the broad application versatility. Utilizing best-in-class adhesives, including repositionables, our facestock and overlaminated constructions provide superior scuff and abrasion resistance, as well as excellent adhesion to a wide range of low surface energy substrates.

## Portfolio Characteristics

- > Reliable adhesion performance on rough, dusty and oily surfaces
- > Strong enough to withstand ongoing outdoor exposure
- > Weather- and temperature-resistant
- > Impervious to contact with aggressive chemicals, oils and gasoline
- > Highly adaptable to varying surface and application conditions
- > A range of cost and performance options
- > Materials suitable for thermal transfer, digital and laser printing

## Featured Construction

A high-performance Safety and Warning label construction is Fasson® 79653, which employs a 2 Mil PET facestock with the Avery Dennison patented rubber hybridized acrylic adhesive, S8049. The 2 Mil PET provides an excellent print surface that performs well in many environmental conditions, while S8049 provides short-term repositionability for easy application. The highly durable construction also offers the potential to eliminate bubbles/blisters from off-gassing.



**LOW  
MOQ**



**Quick QUOTES –  
CALL TODAY**



**RAPID  
SHIPPING**

## Avery Dennison **AD**vantage: Technical Excellence

You can count on members of the Avery Dennison **AD**vantage: Technical Excellence Team to help you find the products and solutions that work for you and your customers. Our technical experts are dedicated to making your next application a success. Our people are there for you, helping with scaleup, converting, application troubleshooting and employee training. We'll put the industry's most comprehensive offering of facestocks, adhesives and liners to work for you in the shortest possible time.

**Are we missing a construction you need?  
Ask about our Select Solutions Engineered  
Solutions.**

Contact your application consultant or sales representative to discuss how we can meet your needs. We have a team of technical solutions leaders dedicated to developing engineered solutions that fit your timeline and your bottom line.

Spec#	Product Description	Width/Length (In./Ft.)	Location	Lead Time
79453	Fasson® 2 Mil White PET TC/S8049/50#SCK	Stock 54/1668	PVL	Next Day
77920	Fasson® 2 Mil White PET TC/S8025/50#SCK	EXACT™/5000	NEE	Next Day
78385	Fasson® 2 Mil White PET TC/S8001/50#SCK	EXACT™/5000	NEE	Next Day
77922	Fasson® 2 Mil Matte Chrome PET TC/S8025/50#SCK	EXACT™/5000	FTW	4 Days
78403	Fasson® 2.3 Mil White BOPP TC/S8001/50# SCK	EXACT™/5000	NEE	Next Day
79653	Fasson® 2 Mil White PET TC/S8049/EZ Liner	Stock 55/2500	PVL	5 Days
79651	Fasson® 4 Mil White Vinyl/S8025/EZ Liner	Stock 55/2500	PVL	5 Days
79246	Fasson® 4 Mil White Vinyl/S8025/50#SCK	Custom Coat/5000	FTW	4 Days
75849	Fasson® 3 Mil Velvet Lexan®/S730/1.5 Mil PET	EXACT™/1668	NEE	Next Day
75850	Fasson® 5 Mil Velvet Lexan®/S730/1.5 Mil PET	EXACT™/1668	NEE	Next Day
79325	Fasson® 1 Mil Clear UV PET/S3000/1.0 Mil PET Over laminate	Stock 60/1668	PVL	Next Day
77843	Fasson® 1 Mil Matte PET/S8020/40#BG Over laminate	Stock 60/1668	PVL	Next Day

NEE=Neenah, WI PVL=Painesville, OH FTW=Fort Wayne, IN

16148, 12/2017, PDF

©2017 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, product names and codes are trademarks of Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. Personal and company names and other information on samples depicted are fictitious. Any resemblance to actual names and addresses is purely coincidental.



Label and  
Packaging Materials

**North Asia**  
5th Floor, Hongye Park  
1801 Hongmei Road,  
Xuhui District 200233,  
Shanghai, China  
+86 21 33951888

**South Asia Pacific and  
Sub-Saharan Africa**  
460 Alexandra Road,  
PSA Building  
#28-02/03, Singapore 119963  
+65 6430 7000

**Europe**  
Willem Einthovenstraat 11  
2342 BH Oegstgeest  
The Netherlands  
+31 85 000 2000

**Latin America**  
Rodovia Vinhedo-  
Viracopos, KM 77  
CEP 13280-000  
Vinhedo - SP, Brazil  
+55 19 3876-7600

**North America**  
8080 Norton Pkwy  
Mentor, OH 44060  
800.944.8511