

Fasson® Fasprint NG Piggyback / Permanent

Product Identification Number: AMA 5050

Facestock:

Fasson® Fasprint NG: A smooth, white, semi gloss all purpose finished sheet with the characteristics necessary for die cutting and stripping

Basis Weight: 80 gsm $\pm$ 10% (ISO 536)

Caliper: 0.066mm $\pm$ 10%

Adhesive:

Fasson® Permanent : A special permanent rubber based adhesive featuring high initial tack and excellent ultimate bond strength to a wide range of substrates.

Minimum Application Temperature : 5° C
(The minimum temperature at which the label can be applied and will adhere)

Service Temperature Range : - 40° C to + 70° C
(The temperature range to which the label can be exposed after the adhesion bond to the substrate has been formed)

Liner:

Fasson® CK40-PB: Two Layers of bleached super calendared kraft liner featuring high internal strength.

Basis Weight : 62 gsm $\pm$ 10% (ISO 536) **(Two layers)**

Caliper: 0.055mm $\pm$ 10% Total Caliper = 110mic

Total Construction Caliper : 0.205 mm $\pm$ 10%

Application and Use: Typical uses for a piggyback product include labels for applications requiring primary label and a secondary label for records. For example, courier packages, vaccination records, tracking labels for corrugated boxes.

Conversion: The product is suited to single and/or multicolour, line or process printing by Letterpress, Offset, Flexo or Screen. A higher gloss finish can be achieved by additional varnishing.

Shelf Life: Two years when stored at 22° C / 50% RH.

As with all self-adhesive materials, this product should be tested thoroughly under end-use conditions to make sure it meets the requirements of the specific application.

Version 1090007iii

Avery Dennison (India) Pvt. Ltd.
Narsinghpur Industrial Area
Six Kilometer stone
Delhi-Jaipur Highway
Gurgaon-122001, Haryana
Tel +91-124—2215581/582/583
Fax +91-124-2215591/592

