

Product data FASSON MC PRIMECOAT S2000N-BG40

Product Code: AA005 Issue date:29-May-2012

FaceStock

A white, one side machine coated, woodfree printing paper with semi-gloss appearance.

Basis Weight 80g/m² ISO 536 ISO 534 Caliper 0.069mm

Adhesive

A general purpose permanent, acrylic based adhesive.

BG40, a supercalendered glassine paper. Basis Weight 59g/m² ISO 536 ISO 534 Caliper 0.053mm ISO 2469 Transparency 50%

Laminate

0.135mm +/- 10% Total Caliper

PERFORMANCE DATA

Initial Tack 700N/m FTM 9 glass Peel Adhes. 90° 300N/m FTM 2 st.st. 0 ℃ Min. appl. temp. Service temp. -20 °C --> +80 °C

N.B.: All data to be considered as typical values.

Adhesive performance

The adhesive is characterized by a high initial tack, excellent adhesion and good low temperature performance on a wide variety of substrates.

The adhesive complies with the European food directives and legislations, FDA 175.105 and the German recommendations XIV as published by BfR. BfR (Bundesinstitut für Risikobewertung) is the German Federal Institute for Risk Assesment. The adhesive can be used in direct contact with dry, non fatty foodstuffs.

Applications and use

The favourable adhesive properties allow the product to be used on a wide range of flat and curved substrates, including packaging materials such as cardboard, plastic films, HDPE, PP and PET.

A trial is always needed to verify the product / end use suitability.

Conversion / Printing

Facestock is suitable for single and/or multicolour line or process printing by letterpress, offset, flexo, screen and hot foil stamping.

If required the labels can be upgraded to a higher gloss level by additional varnishing.

Excellent conversion characteristics in flat-bed and rotary on wide-web presses with high conversion speeds.

Shelf life

Two years, stored at 22 °C / 50% RH.

Toll Free: 08000 AVERY Fax: 0860 AVERY Johannesburg Tel: +27 11 249 5700 Fax: +27 11 472 2715

Durban

Europe

South Africa Tel: +27 11 249 5700

Fax: +27 11 472 2770

Tel: +852 2802 9618 Fax: +852 2588 1344

Asia Pacific

Tel: +27 21 534 0985 Fax: +27 21 534 0986

Tel: +27 31 792 6400 Fax: +27 31 792 6416

South America Tel: +317 1 579 4100 Fax: +317 1 579 4180

North America Tel: +54 11 4014 2200 Fax: +54 11 4014 2225

Tel: +800 944 8511 (U.S. & Canada) Tel: +52 55 5565 0100 (Mexico)

Warranty

Information concerning Products are based upon tests believed to be reliable but do not represent a guarantee or warranty. Products are provided on the basis that any Purchaser has independently determined the suitability of the Products and Purchaser's purposes. The Company warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year of delivery (but not afterwards), upon notification thereof within seven (7) days of such appearance and substantiation that the Products have been stored and applied in accordance with the Company standards, the Company shall within a reasonable period correct such defects by providing a suitable replacement without charge at the Company's plant or at the location of the Products (at the Company's election) provided however, if the Company in its sole discretion determines that replacement is not commercially practical, the Company may issue a credit in favour of the Purchaser in an amount not to exceed the purchase price actually paid for the Products. Any implied warranty of merchantability fitness for particular purpose or other warranty of quality, whether express or implied by law, is hereby excluded to the extend permitted by law. In no event shall the Company be liable for any incidental, indirect or consequential damages including, but not limited to, loss of profit, loss of use or loss of capital. The remedies of the Purchaser set forth herein are exclusive, and the total potential liability of the Company arising out of any contract of or from the manufacture, sale, delivery, resale, installation or use of any products shall not exceed the purchase price of the products upon which liability is based.