
**Fasson® Dull Silver Laminated Foil ITC (Indigo Top Coat)
/C2500/40#SCK**

Spec# 19979

Facestock:

Fasson® Dull Silver Foil ITC (Indigo Top Coat) is an aluminum foil laminated to a white kraft base sheet, with an acrylic topcoating for printability. Good printing with solvent/water-based flexo. Not recommended for imprinting.

Basis Weight:	70# per ream \pm 10% (500 sheets 25" x 38")
Caliper:	0.0037 inches \pm 10%
Tensile:	MD 27# per inch width CD 15# per inch width
Tear:	MD 45 grams per sheet CD 50 grams per sheet
Stiffness:	MD 250 mg CD 160 mg

Adhesive:

Fasson® C2500 is a rubber-based adhesive featuring high initial tack and ultimate bond strength to a wide variety of substrates, including low surface energy plastics, treated glass, and corrugated cardboard. The 25° F minimum application temperature covers the vast majority of prime label requirements. Fasson® C2500 features excellent high speed/wide web converting characteristics. Fasson® C2500 is suitable for applications where compliance with FDA 175.105 is required. This section covers applications where incidental contact between food and adhesive could occur.

Type:	Hot Melt Rubber
Minimum Application Temperature:	+25° F
Service Temperature Range:	-65° F to +160° F

Typical Performance Data: Using 60# Semi-Gloss Elite™ facestock, at room temperature.

HDPE

Loop Tack:	4.71 lbs
Peel Adhesion:	3.72 lbs

Polypropylene

Loop Tack:	4.60 lbs
Peel Adhesion:	2.62 lbs

Glass - PE treated

Loop Tack:	2.34 lbs
Peel Adhesion:	2.34 lbs

Shrink film

Loop Tack:	2.88 lbs
Peel Adhesion:	2.31 lbs

Recycled corrugated

Loop Tack:	1.57 lbs
Peel Adhesion:	1.81 lbs

Liner:

40#SCK is a bleached super-calendered kraft stock featuring high internal strength, toughness, and tear resistance. Used primarily for roll-to-roll label applications.

Basis Weight:	42# per ream \pm 10% (24" X 36" 500 sheets)
Caliper:	0.0025 inches \pm 10%
Tensile:	MD 38# per inch width CD 20# per inch width
Tear:	MD 36 grams

CD 41 grams

Total Construction Caliper (approximate): 0.0070 inches \pm 10%

***HP Indigo Certified for the ws 4000 series and the ws 6000 industrial roll -fed presses .**

Shelf Life

Unless specified otherwise in this document , one year when stored at 72°F at 50% RH

Statement of Practical Use

All pressure-sensitive materials should be tested thoroughly under end -use conditions to ensure they meet the requirements of the specific application .

Warranty

All sales and contracts for sale are expressly conditioned on the buyer's assent to Avery Dennison's terms and conditions found on its website at www.na.fasson.com. Avery Dennison hereby objects to any term, different from or additional to Avery Dennison's terms, contained in any buyer communication in any form, unless agreed to in a writing signed by an officer of Avery Dennison.

www.na.fasson.com



Label and Packaging Materials -North America

8080 Norton Parkway
Mentor, OH 44060
800-944-8511

