

# Facestock

A gloss white polyester film with a receptive top coat and covert "void" feature.

Basis Weight	82 g/m²	ISO 536
Caliper	60 µm	ISO 534

# Adhesive

A permanent, acrylic based adhesive.

# Liner

BG45 white, a supercalendered glassine paper.

Basis Weight	73 g/m²	ISO 536
Caliper	62 µm	ISO 534
Transparency	50 %	DIN 53147
Laminate		
Total Caliper	142 µm±10%	ISO 534
Performance data		
Initial Tack	14.5 N/25mm	FTM 9 Glass
Peel Adhesion 90°	9 N/25mm	FTM 2 St.St.
Min. Application Temp.	5 °C	
Service temperature	-40°C to 90°C	

### Adhesive Performance

The adhesive is perfectly suitable for uses that need a good resistance to UV, drippings or solvents. Good general adhesion performance on a wide range of substrates.

### Applications and use


Once applied to the substrate on removal, an irreversible "void" fooprint message - formely invisible to the eye - will detach itself from the face film. Labels which have been removed cannot be reapplied since repositioning will leave visible proof that tampering has taken place.

#### Shelf life

One year under storage conditions as defined by FINAT (20- $25^{\circ}C$ ; 40-50%RH)

# AB176

# Fasson ® VOID PET50 WHITE - S697-BG45WH



# VOID PET50 WHITE

S697

BG45WH

This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.

If you would like to make a suggestion or comment on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com

### **Avery Dennison Materials Group Europe**

Willem Einthovenstraat 11 2342 BH Oegstgeest The Netherlands +31 (0)85 000 2000

#### Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes.

Avery Dennison products are warranted to be free of defects in material or workmanship for a period of one year from the date of shipment. Should a defect be communicated to Avery Dennison within that time frame, Avery Dennison will evaluate and determine the existence of the defect and further decide, at its sole discretion, to either replace the defective product without charge or compensate it with a credit note in such amount as



ANY OTHER WARRANTY, WHETHER EXPRESS OR IMPLIED, OR WHETHER OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR OTHERWISE, SHALL BE EXCLUDED. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND SIGNED BY AN EXECUTIVE OFFICER OF AVERY DENNISON.

©2013 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or



Avery Dennison deems reasonable. Avery Dennison shall have no responsibility beyond the replacement value of the defective product nor shall in any way be liable or responsible for consequential or incidental damages.

reproduced in whole or in part for any purposes other than marketing by Avery Dennison.